

What are the screening specifications for ceramic ferrules



Overview

Two common ferrule materials—zirconia ceramic and lower-cost plastic composites—provide comparable performance and achieve compliance with TIA/EIA-568-B. 3 requirements (Insertion Loss <0 . Ceramic ferrules and sleeves are often used in optical connectors, attenuators, fiber stubs, and other optoelectronics requiring low signal loss. Kyocera's extrusion molding process creates ferrules with excellent coaxiality, and our precision machining ensures excellent concentricity with precise. This standard was developed to guide the fiber-optic industry in determining what kind of defects could be on the ferrule end face with no negative performance impact. However, the ability of each connector type to maintain physical contact can differ. The family of patented precast ferrule systems provide more effective protection and increased design flexibility than traditional refractory systems due to the separation of the structural and insulating functions that are addressed by the cast shape and the fiber backup, respectively. Custom Ferrules are made of alumina or zirconia ceramics, with inside diameters from 80 microns to 1100 microns, in lengths from 2. 5mm. post polishing failures. The document is intended to inform and educate about polishing processes and commercial automated polishing equipment with various fixturing in order to achieve a stable low insertion loss, targeted return loss, acceptable 3D endface geometry, and defect free visual fiber.

Article Content

Apr 04, 2026

Stud Welding Ceramic Ferrule Dimensions

Determine the ferrule specifications for each type of standard ferrule: Flat, Heavy Duty, Thru Deck, Collar, Pitch Diameter/Partial Thread or Angle Combo

Feb 23, 2026

Fiber Optic Ceramic Ferrule-Fiber Optic MPO Ferrule-MT Ferrule-JFOPT

All the ceramic ferrule adopted in JFOPT's is from CCTC, which have higher precision and more accurate micro size and appearance. The high-quality ferrule is the key of high stability and better ...

Dec 11, 2025

Ceramic Ferrules / Sleeves | Ceramics for Optical Connectors | Ceramic ...

Our ferrules and sleeves are available in standard size and shape configurations. For standard products, please see the following. Kyocera can machine the end face of the ferrule based on the customer's ...

Mar 15, 2026

Blasch ProLok Ferrules-Ceramic Two Piece.pdf

Blasch's ProLok ferrules are available with a wide range of tapered inlet and outlet profiles. In addition to reducing the refractory mass in the furnace, ProLok ferrules have been shown to reduce pressure ...

Dec 03, 2025

Polishing Best Practices

lished ceramic ferrules. The standards are largely similar, with minor exceptions, and they are summa ized in the table below. For instance, GR-326 is more stringent in terms of the ROC range, upper ...

Jun 29, 2026

Ceramic Ferrules / Sleeves | Ceramics for Optical ...

Our ferrules and sleeves are available in standard size and shape configurations. For standard products, please see the following. Kyocera can machine the end face ...

May 06, 2026

Ferrule spec docs | PRODUCTS | SEIKOH GIKEN

Please contact us directly for any other specifications not listed in this page. Adobe Reader is required to open the pdf files above. [Click here to download a free copy.](#)

Jul 13, 2026

Ceramic Ferrules

Standard singlemode and multimode ceramic sleeves are typically used for FC, ST, SC, LC, and SMA connectors and ferrules. We also offer custom split and solid sleeves made to your exact specifications.

Jul 07, 2026

Ceramic Ferrule Specifications

SN10 10.7 ± 0.35 14.8 ± 0.40 13.3 ± 0.35 18.1 ± 0.45 5.3 ± 0.20 10.1 ± 0.35 4.0 ± 0.15 16
 SR10 10.7 ± 0.35 15.0 ± 0.40 18.1 ± 0.45 7.0 ± 0.25 11.0 ± 0.35 12 SN13 13.4 ± 0.40
 $18.6 \pm 0. ...$

Aug 13, 2025

Clean & Inspect: What IEC 61300-3-35 Means to You

The Industry Standard Contamination Types Inspect, Clean, Inspect Static Charge Problems Sources of Static Solving The Static Problem Cleaning at What Cost? Invest in A Quality Cleaning Fluid Replace The Paper Wipes Avoid Water The more common end face defect that field installers encounter is generally termed "debris." Debris is dust, lint, plastic or ceramic particulate, fingerprint oils or a host of other contamination. The industry's best practice is to remove all debris from both connector end faces using optical-grade cleaning materials before mating the connectors. See more on microcare hc-cera .tw

Ceramic Ferrule Specifications

SN10 10.7 ± 0.35 14.8 ± 0.40 13.3 ± 0.35 18.1 ± 0.45 5.3 ± 0.20 10.1 ± 0.35 4.0 ± 0.15 16
 SR10 10.7 ± 0.35 15.0 ± 0.40 18.1 ± 0.45 7.0 ± 0.25 11.0 ± 0.35 12 SN13 13.4 ± 0.40
 $18.6 \pm 0. ...$

Sep 18, 2025

Fiber Optic Connectors

Ceramic ferrules are well known for having high durability and the highest levels of dimensional control, making them suitable for use in all fiber applications (both singlemode and multimode) specified in ...

Mar 28, 2026

Clean & Inspect: What IEC 61300-3-35 Means to You

This standard was developed to guide the fiber-optic industry in determining what kind of defects could be on the ferrule end face with no negative performance impact.

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.chromadecksigns-eastrand.co.za>

Email: sales@chromadecksigns-eastrand.co.za

Phone: +32 2 318 5792

Address: Avenue Louise 500, 1050 Brussels, Belgium

This document is for informational purposes only. Specifications subject to change without notice.

